

Steam

STOPPER

A translucent cap for your shower

This product has been checked in our factory prior to dispatch, however we encourage you to check for any transport or manufacturing defects. If any manufacturing defects or damage is discovered, then please refer this issue to the retailer from which you bought this product. Should trimming of your Steam Stopper be required, perhaps due to out of square walls or special features with your particular shower, the recommended methods of trimming must be followed, see page 3. All trimming must be undertaken on a clean/flat surface where the Steam Stopper product can be sufficiently supported to stop any movement.

What? How? Why?

What? Is a steam stopper

Every household has the common problem of condensation & steam build up in their bathroom. To eliminate this issue, an easy DIY product with a durable translucent finish, which actually stops steam being generated, was created.

How? Does it work

Without using a steam stopper, the cold air mixes with the hot moist air that rises from within your shower, which is how condensation & steam is created in the first place.

So the purpose of using a steam stopper that sits on top of your shower, is to keep the **hot air in** and the **cold air out**. This increases the temperature inside the shower, therefore using less hot water due to running your shower cooler. This can reduce your hot water heating costs as well.

Why? Benefits

- Eliminates condensation in your shower enclosure & bathroom
- No mould growth, means improved air quality
- Therefore this extends the life of your painted/wallpapered walls
- No misting of bathroom mirror
- Reduces the need for an extractor fan &
- Increases shower enclosure temperature – therefore can reduce your hot water usage

To Install your Steam Stopper

The steam stopper is an easy DIY product which is very easy to install – no installer required. It has easy to fit brackets which support the steam stopper when placed on top of your shower.

Step by step instructions on how to install your Steam Stopper

Step 1: Check dimensions of Steam Stopper, by placing it on top of the shower, and confirm the Steam Stopper sits evenly on the shower – trim if necessary.

Trimming of your Steam Stopper: This must be undertaken on a clean/flat surface where the Steam Stopper product can be sufficiently supported to stop any movement. Recommended options of trimming are discussed below, see page 3.

Step 2: Establish where the support brackets need to be attached – minimum of 3 brackets for a 3 sided shower & 2 brackets for a 2 sided shower. Centrally locate the bracket along each long edge of the Steam Stopper.

Step 3: Hold brackets in required position and drill pilot holes through shower wall. A small amount of silicone can be applied to holes to improved water tightness prior to screwing bracket on.



Step 4: Using screws provided, attach brackets to the shower wall. Snap on the cover plate when securely fixed.



Step 5: Now simply place the Steam Stopper onto your Shower & enjoy your showering experience. No fixing of the Steam Stopper product to the top of your shower is required. In fact, the easy removal of this product for cleaning is one of its strongest features.



Recommended options of trimming are:

All trimming must be undertaken on a clean/flat surface where the Steam Stopper product can be sufficiently supported to stop any movement.

Routing

This product can be routed by first fully supporting the product marking the trim line where required, and then using a guide to trim along the edge in a smooth and fluid motion. You can clean up the acrylic edges by using sandpaper to create a smooth finish.



Fine tooth hand saw

This product can be trimmed with either a fine tooth hand saw, coping saw or hack saw. You must always support the Steam Stopper product on a clean & flat surface, to stop any movement of the product as it is sawn. Once again, you can clean up the acrylic edges by using sandpaper to create a smooth finish



Belt Sander for minor alterations

A belt sander can be used to remove small amounts of material.



Drilling

If any drilling is required, the Steam Stopper product can be drilled with any standard drill bit. The best results are achieved without the use of a pilot hole. Please select the correct size drill bit and drill applying an even moderate amount of pressure into the plastic & supported onto a block of timber or other suitable surface.

Cleaning your Steam Stopper

Please clean your Steam Stopper with a soft cloth and warm water. A spray on window cleaner and soft cloth can be used to remove light staining. For heavier staining, it can be removed with liquid jiff and a soft cloth, followed by a spray on window cleaner and soft cloth.

Under no circumstances should any form of abrasive cleaners be used.